



## H.265 + IVR

### 主要功能

- 最新H.265+ 影像壓縮技術
- 即插即用
- 支援虛擬網路
- 支援Mini CMS
- 支援POE(IEEE 802.3af)

4K

H.265+








H.264

SATA

DDNS



# H.265+ IVR

型號		IVR-0461UC-1 Ultra	IVR-0461UM-4 Ultra	IVR-0861UC-1 Ultra	IVR-0861UM-4 Ultra	IVR-1681UA-N Ultra	IVR-2581UA-B Ultra	IVR-3281UA-B Ultra	
圖例									
外殼		1	4	1	4	N	B		
影像	輸入	4CH		8CH		16CH	25CH	32CH	
	頻寬	Max. 70Mbps				Max. 256Mbps			
	影像支持格式	Max. 8MP@30/25fps · 5MP@30/25 fps · 4MP@30/25 fps · 3MP@30/25 fps · 1080P@30/25 fps · 720P@30/25 fps (ONVIF 2.4)							
	多重即時與回放頻道	720P @ 30 fps · VGA @ 30 fps							
	影像輸出接口	1 HDMI (Max. 3840 x 2160) with Audio				1 HDMI (Max. 3840 x 2160) with Audio and 1 VGA ( Max. 1920x1080)			
聲音	輸入	1							
	輸出	1							
系統	使用系統	Embedded Linux OS							
	晶片型號	Hi3798M				Hi3536			
	影像壓縮格式	H.264/H.265							
	SATA 裝置	Max. 1 x SATA Devices				Max. 3 x SATA Devices		Max. 7 x SATA Devices	
	外接硬碟	eSATA							
	輸入點偵測繼電器	-	Alarm-in x 4 Relay-out x 1	-	Alarm-in x 4 Relay-out x 1	Alarm-in x 16 Relay-out x 2	Alarm-in x 16 Relay-out x 4		
	IO介面	-							
	USB 埠	USB 2.0 x2				USB 2.0 x2 , USB 3.0 x1			
	尺寸	250(w)x45(h)x215(d)	354(w)x45(h)x230(d)	250(w)x45(h)x215(d)	354(w)x45(h)x230(d)	430(w)x55(h)x293(d)	442(w)x92(h)x438(d)		
	電壓	DC 48V 2A 96W Adapter 110/220V		DC 48V 3.25A 156W Adapter 110/220V		AC 110/220V 300W With 48V (PoE)			
顯示	分割畫面	1, 4, SEQ.		1, 4, 9, SEQ.		1, 4, 9, 13, 16 SEQ.	1, 4, 9, 13, 16, 25 SEQ.	1, 4, 9, 13, 16, 25, 32 SEQ.	
	自動跳台	Switching time : 1 ~ 99 sec							
	模式	Zoom, PIP, Auto SEQ.							
錄影	網路攝影機輸入格式 (60Hz /50Hz DUHD攝影機)	Max. 8MP@30/25fps · 5MP@30/25 fps · 4MP@30/25 fps · 3MP@30/25 fps · 1080P@30/25 fps · 720P@30/25 fps							
	模式	Continuous, Event, Schedule							
回放	搜尋模式	Date/time, Event							
	放大	*Digital ( x2 ~ x5 )							
網路	網路串口	1x RJ45 Ethernet port (10/100Mbps)				1x RJ45 Ethernet port (10/100/1000Mbps)			
	網路線供電	IEEE802.3af (4 Ports)		IEEE802.3af (8 Ports)		IEEE802.3af (16 Ports)			
	通訊協定	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS, FTP, SMTP							
	Onvif	YES							
	遠端控制軟體	Socatch DVR, IE Browser, iCMS							
	使用者帳戶	1 Admin + 10 Users							
	行動裝置支援	iPhone, iPad, Android				Windows Phone, iPhone, iPad, Android			
備份	外接介面	USB2.0				USB			
	聲音備份	YES							
	備份介面	Network, Ext. USB flash device etc							
警報	事件日誌	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)							
功能系統	多國語言	Supported							
	觸控螢幕	-				Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)			
	系統更新	USB Flash Drive, iWatch DVR							
一般	操作溫度	0°C ~ +55°C (32°F ~ 131°F)							
	操作濕度	10%~80%				10%~90%			

All specifications are subject to change without notice.

